



NOTES:

1. ALL DIMENSIONS ARE IN MILLIMETERS.
DIMENSIONS SHOWN ARE PROJECTED DISTANCES.
2. GLASS THICKNESS: 3 mm NOMINAL.
3. TRANSDUCERS ARE LOCATED AT THE POSITIONS SHOWN.
GLASS IS BEVELED UNDER TRANSDUCERS.
4. CABLES ARE ROUTED ALONG THE EDGE OF THE GLASS.
5. THE TOUCH ACTIVE AREA IS LESS THAN THE VIEWABLE AREA TO FACILITATE SEALING.
6. ARRAY PATTERNS ARE CENTERED ON GLASS WITH A TOLERANCE OF ± 1.3 mm.

| CONNECTION CHART | | | |
|------------------|-------------|------------------|--------------|
| PIN | SIGNAL | INSULATION COLOR | JACKET COLOR |
| 1 | GROUND | OVERALL SHIELD | |
| 2 | KEY | | |
| 3 | Y RECEIVE+ | BLU | BLK |
| 4 | Y TRANSMIT+ | BLU | GRY |
| 5 | Y RECEIVE- | BLK | BLK |
| 6 | Y TRANSMIT- | YEL | GRY |
| 7 | GROUND | INNER SHIELD | |
| 8 | X TRANSMIT- | RED | RED |
| 9 | X RECEIVE- | RED | BLK |
| 10 | X TRANSMIT+ | GRN | RED |
| 11 | X RECEIVE+ | WHT | BLK |
| 12 | KEY | | |

| | | |
|---|-----------------------|----------------------------|
| 宇鴻光電股份有限公司 ATouch Technologies Co., Ltd. | | |
| P/N: SAW151S2G1 | | |
| DRAWN BY KEN | DIMENSION UNIT mm | ISSUE DATE 03 / 31 / 07 |
| CHECKED BY MELISSA | SCALE NOT TO SCALE | REV E |